



U.S. Department  
of Transportation

**Pipeline and  
Hazardous Materials  
Safety Administration**

400 Seventh Street, S.W.  
Washington, D.C. 20590

**MAR 29 2005**

DOT-E 7657  
(TWENTIETH REVISION)

EXPIRATION DATE: February 28, 2007

(FOR RENEWAL, SEE 49 CFR § 107.109)

1. GRANTEE: Welker Engineering Company  
Sugar Land, TX
2. PURPOSE AND LIMITATIONS:
  - a. This exemption authorizes the manufacture, mark, sale and use of non-DOT specification stainless steel cylinders conforming with all regulations applicable to a DOT specification 3E cylinder, except as specified herein, for the transportation in commerce of the materials authorized by this exemption. This exemption provides no relief from the Hazardous Materials Regulations (HMR) other than as specifically stated herein.
  - b. The safety analyses performed in development of this exemption only considered the hazards and risks associated with transportation in commerce.
3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171-180.
4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR §§ 173.201, 173.202, 173.203, 173.302a(a)(1), 173.304a(a)(1), (a)(2), (b), and 175.3 in that non-DOT specification cylinders are not authorized except as specified herein; §§ 173.301(f)(2) and 177.840(a)(1) in that the pressure relief device on the product side of the cylinder is in contact with liquid product at all times.

MAR 29 2005

5. BASIS: This exemption is based on the application of Welker Engineering Company dated March 1, 2005 submitted in accordance with § 107.109.

6. HAZARDOUS MATERIALS (49 CFR § 172.101):

Hazardous Material Description			
Proper Shipping Name	Hazard Class/Division	Identification Number	Packing Group
1,2-Dichloro-1,1,2,2-Tetrafluoroethane or Refrigerant gas R 114	2.2	UN1958	N/A
Air, compressed	2.2	UN1002	N/A
Ammonia Solutions, relative density less than 0.888 and 0.957 at 15 degrees C in water, with more 35 percent but not more than 50 percent ammonia	2.2	UN2073	N/A
Butane see also Petroleum gases, liquefied	2.1	UN1011	N/A
Carbon dioxide	2.2	UN1013	N/A
Compressed gas, flammable, n.o.s. (Crude oil under pressure)	2.1	UN1954	N/A
Compressed gas, toxic, n.o.s. Inhalation Hazard Zone D	2.3	UN1955	N/A
Compressed gas, toxic, flammable, n.o.s. Inhalation Hazard Zone D	2.3	UN1953	N/A
Dichlorodifluoromethane or Refrigerant gas R 12	2.2	UN1028	N/A
Ethane	2.1	UN1035	N/A
Gasoline	3	UN1203	II
Helium, compressed	2.2	UN1046	N/A

MAR 29 2005

Hazardous Material Description			
Proper Shipping Name	Hazard Class/ Division	Identification Number	Packing Group
Hydrocarbons, liquid, n.o.s.	3	UN3295	I, II, III
Isobutane see also Petroleum gases, liquefied	2.1	UN1969	N/A
Isopropanol or Isopropyl alcohol	3	UN1219	II
Kerosene	3	UN1223	III
Liquefied gas, toxic, flammable, n.o.s.*	2.3	UN3160	N/A
Liquefied gas, flammable, n.o.s.	2.1	UN3161	N/A
Liquefied gas, n.o.s.	2.2	UN3163	N/A
Methane, compressed or Natural gas, compressed (with high methane content)	2.1	UN1971	N/A
Nitrogen, compressed	2.2	UN1066	N/A
Oil gas, compressed	2.3	UN1071	N/A
Petroleum crude oil	3	UN1267	I, II or III
Petroleum distillates, n.o.s. or Petroleum products, n.o.s.	3	UN1268	I

MAR 29 2005

Hazardous Material Description			
Proper Shipping Name	Hazard Class/ Division	Identi- fication Number	Packing Group
Petroleum gases, liquefied or Liquefied petroleum gas	2.1	UN1075	N/A
Propane also see Petroleum gases, liquefied	2.1	UN1978	N/A

**NOTES:**

\* Applicable parts of § 173.40 must be complied with when transporting this material.

Other materials must be specifically identified to, and acknowledged in writing, by the Office of Hazardous Materials Exemptions and Approvals (OHMEA) prior to the first shipment.

**7. SAFETY CONTROL MEASURES:**

a. PACKAGING - Packaging prescribed is a stainless steel non-DOT specification cylinder having a marked service pressure of 1800 psi, constructed from seamless stainless steel tubing, with threaded end caps or with flanged flat head end closures at each end restrained by tie rods, and containing a floating piston which forms two pressure chambers. Cylinder must conform with Welker Engineering sketches, photographs, drawings and calculations on file with the Office of Hazardous Materials Exemptions and Approvals and with DOT 3E specification (§§ 178.35 and 178.42) except as follows:

§ 178.35(e) *Safety devices.*

(added) Each head must be equipped with safety relief devices.

§ 178.35(f) *Markings.*

Applies except marking "DOT-E 7657" in lieu of "DOT 3E".

**MAR 29 2005**§ 178.35(g) *Inspector's report.*

(added) The inspector's report may be revised to accommodate the tests required by this exemption. A copy of the inspector's report on the first lot out of each design must be submitted to the OHMEA prior to shipment of the cylinders.

§ 178.42(a) *Type, size and service pressure.*

Seamless cylinder conforming with the following:

(1) Model CP-2 piston style receptacle has flat heads on each end restrained with tie rods secured at each end by nuts or with tie rods threaded into an end cap and secured by nuts on the other end; maximum volume must not exceed 1,000 cc.

(2) Model CP-4 piston style receptacle has threaded flat end caps on each end without tie rods; maximum volume is 100 cc.

(3) Dimensions are as follows:

<u>Model Nos.</u>	<u>No. and size of tie rods.</u>	<u>Maximum O.D. x length</u>	<u>Minimum Side wall thickness (inch)</u>
CP-2-50 thru CP-2-1000	6 x 3/8" OD	2.0" x 29"	.105 if threaded, .083 if not threaded.
CP-4-15 thru CP-4-100	none	1.25" x 14"	.074 if threaded, .055 if not threaded.

§ 178.42(b) *Steel.*

All cylinder components must be SA-240 type 304 or 316 stainless steel.

**MAR 29 2005**§ 178.42(f) *Hydrostatic test.*

Hydrostatic test must be as follows:

- (1) Each compartment of each piston style receptacle must be subjected to a pneumatic test of at least 500 psi without leakage.
- (2) Each cylinder (seamless tube with end caps but without pistons, and with tie bolts, if applicable) must be tested to a hydrostatic test of 3,600 psig and show no defect.
- (3) In addition, one cylinder (seamless tube with end caps but without pistons, and with tie bolts, if applicable) out of each lot of 500 cylinders or less must be pressurized to failure. The pressure at which the cylinder fails to hold test pressure must be recorded. This pressure must not be less than 5,000 psi. Rate of pressurization must not exceed 200 psi per second.
- (4) The tube body of one cylinder from each lot that has passed the tests prescribed in § 178.42(f)(2) of this exemption, must be flattened to at least 10 times wall thickness without cracking.

§ 178.42(g) *Leakage test.*

Does not apply.

b. TESTING - Each cylinder must be visually reinspected at least once a year for deterioration of seals, scratches, dents and gouges. The end caps, tie rods and indicating rods must be thoroughly cleaned with an appropriate solvent recommended by the manufacturer.

c. OPERATIONAL CONTROLS -

- (1) Each cylinder must be shipped in outside packagings in accordance with § 173.301(a)(9).
- (2) The cylinder may be used only for materials that are being transported for purposes of analytical testing.

**MAR 29 2005**8. SPECIAL PROVISIONS:

a. In accordance with the provisions of Paragraph (b) of § 173.22a, persons may use the packaging authorized by this exemption for the transportation of the hazardous materials specified in paragraph 6, only in conformance with the terms of this exemption.

b. A person who is not a holder of this exemption, but receives a package covered by this exemption, may reoffer it for transportation provided no modifications or changes are made to the package and it is offered for transportation in conformance with this exemption and the HMR.

c. A current copy of this exemption must be maintained at each facility where the package is offered or reoffered for transportation.

d. Each packaging manufactured under the authority of this exemption must be marked with a registration symbol designated by the Office of Hazardous Materials Exemptions and Approvals for a specific manufacturing facility.

e. A current copy of this exemption must be maintained at each facility where the package is manufactured under this exemption. It must be made available to a DOT representative upon request.

f. Transportation of Division 2.1 (flammable gases) materials and Division 2.3 (gases which are poisonous by inhalation) materials are not authorized aboard cargo vessel or aircraft unless specifically authorized in the Hazardous Materials Table (§ 172.101).

9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle, rail freight, cargo vessel, cargo aircraft only (see restrictions in paragraph 8.f.)

10. MODAL REQUIREMENTS: A current copy of this exemption must be carried aboard each cargo vessel, aircraft or motor vehicle used to transport packages covered by this exemption. The shipper must furnish a current copy of this exemption to the air carrier before or at the time the shipment is tendered.


11. COMPLIANCE: Failure by a person to comply with any of the following may result in suspension or revocation of this exemption and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 et seq:
- o All terms and conditions prescribed in this exemption and the Hazardous Materials Regulations, Parts 171-180.
  - o Persons operating under the terms of this exemption must comply with the security plan requirement in Subpart I of Part 172 of the HMR, when applicable.
  - o Registration required by § 107.601 et seq., when applicable.

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this exemption must receive training on the requirements and conditions of this exemption in addition to the training required by §§ 172.700 through 172.704.

No person may use or apply this exemption, including display of its number, when the exemption has expired or is otherwise no longer in effect.

12. REPORTING REQUIREMENTS: Shipments or operations conducted under this exemption are subject to the Hazardous Materials Incident Reporting requirements specified in 49 CFR §§ 171.15 - Immediate notice of certain hazardous materials incidents, and 171.16 - Detailed hazardous materials incident reports. In addition, the grantee(s) of this exemption must notify the Associate Administrator for Hazardous Materials Safety -- OHMEA, in writing, of any incident involving a package, shipment or operation conducted under terms of this exemption.

Issued in Washington, D.C.:

  
\_\_\_\_\_  
Robert A. McGuire  
Associate Administrator for  
Hazardous Materials Safety

fn

**MAR 29 2005**  
\_\_\_\_\_  
(DATE)



**MAR 29 2005**

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Pipeline and Hazardous Materials Safety Administration, Department of Transportation, Washington, D.C. 20590. Attention: DHM-31.

Copies of this exemption may be obtained by accessing the Hazardous Materials Safety Homepage at <http://hazmat.dot.gov/exemptions> Photo reproductions and legible reductions of this exemption are permitted. Any alteration of this exemption is prohibited.

PO: cwf/sln